


(43)Date of publication of application : 19.04.1988

B01D 13/01
A61K 35/14
B01D 13/04

(72)Inventor : IWATA MICHITAKA
IJIMA HIDEKI

formed from said cellulose. The A-part at one end of the hollow fibers 1 is embedded in a filler 2 and the B-part at the other end thereof is hermetically sealed to form a hollow fiber structure: One end of a tubular body 3 is perfectly sealed to one end part A and united with a joint part 4 mountable to a syringe. The open end part of the tubular body 3 to the external system is made present in the same plane as the position of one end part B. In use, the syringe is inserted in the joint part 4 and one end part B is directly inserted in a drug bottle receiving a blood (plasma) preparation to suck said preparation by the syringe.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

XP-002247182

AN - 1988-145060 [21]

A - [001] 014 04- 252 253 43& 481 51& 528 540 56& 575 58& 595 596 623 624
643 645

AP - JP19860233257 19861002

CPY - ASAH

DC - A88 D15 D22 J01

FS - CPI

IC - A61K35/14 ; B01D13/01

KS - 0231 1982 2653 2654 2676 2765 2768 3245 3256 3270

MC - A03-A05A A12-S05A A12-V03B A12-W11A D04-A01E D09-A02 J01-C03 J01-E03E
J01-F02B

PA - (ASAH) ASahi CHEM IND CO LTD

PN - JP63088007 A 19880419 DW198821 007pp

PR - JP19860233257 19861002

XA - C1988-064809

XIC - A61K-035/14 ; B01D-013/01

AB - J63088007 Module comprises porous and regenerated cellulose hollow
fibres made by the copper ammonium process, the fibres satisfy the
formula

- $\phi = 0.5 \times 10 (3.01 \times 10 \text{ power } -3 V - 2.34 \times 10 \text{ power } -2 D) \times T (l)$

- where ϕ is the checking coefficient which = 3. An end (A) of the
fibre is embedded in filler and opened to the outside and the other
end (B) is sealed or embedded in the filler at the same position. The
hollow fibre structure is fitted in a tubular body opened at one end.
The end of the tubular body and that of the hollow fibre are in the
same plane, and one end side of the fibre has a joint attachable with
an injector, where V is virus gp. (nm); D is water flow velocity mean
bore (nm) and T is film thickness (micro-m).

- ADVANTAGE - The module removes viruses causing diseases without losing
major protein component in blood plasma. Time series variation of
filtration speed is small and filtering is rapid. Virus free
filtration liq. is easily recovered in the injector directly.(0/3)

IW - VIRUS FREE MODULE FLUID SEPARATE ULTRAFILTER COMPRISE POROUS HOLLOW
REGENERATE CELLULOSE FIBRE SPECIFIC CHECK COEFFICIENT FIT TUBE BODY
OPEN ONE END

IKW - VIRUS FREE MODULE FLUID SEPARATE ULTRAFILTER COMPRISE POROUS HOLLOW
REGENERATE CELLULOSE FIBRE SPECIFIC CHECK COEFFICIENT FIT TUBE BODY
OPEN ONE END

NC - 001

OPD - 1986-10-02

ORD - 1988-04-19

PAW - (ASAH) ASahi CHEM IND CO LTD

TI - Virus-free module or fluid separator for ultrafiltration etc. -
comprises porous and hollow regenerated cellulose fibres having
specific checking coefficient and fitted in tubular body open at one
end